

Product Specification Sheet



FS2-250A

A robust modular power distribution enclosure made from galvanised sheet steel rated to 250A. This freestanding MOD.DU enclosure comes with a heavy duty stand suitable for crane lifting or placement by forklift or pallet truck. The MOD.DU enclosures are used for temporary power distribution for environments such as construction sites and other heavy industrial areas. These units are manufactured to the requirements of BS EN 61439-4.

Featuring a 250A 4P Schneider MCCB incomer, located in a segregated end box, consisting of 5x test lead sockets to enable safer onsite testing. The 10W MOD.DU busbar assembly sits within a 700mm width enclosure, compatible with a variety of distribution module options, including; hardwire MCCB/RCD subcircuits ranging from 125A-630A, direct connect modules to create a tower crane switch or plant RCD from 125A-630A, segregated 160A MCB modules and commando socket, outlet modules and powerlock modules to create a secure plug and play system. MOD.DU Modules, blanks and additional accessories are purchased separately.



21-11-2024 | 18:00:11

EL-BJORN UK LTD

Unit 2 Oyster Park, 109 Chertsey Road,
West Byfleet, GB-Surrey, KT14 7AX
Phone: (+44) 01483 729 348
E-mail: info@elbjorn.com



Product Benefits

- Customisable, Modular Power Distribution Units
- Galvanised sheet steel with powder coating finish
- Integral fork pockets and vertical crane lifting accessories
- 10 Module Ways
- Contact us directly for purchases

Technical Data

| | |
|---------------------------|--|
| Product name | FS2-250A |
| Product Number | EB16741 |
| Colour | El-Björn Blue |
| Dimensions H x W x D (mm) | 1700 x 700 x 500 |
| Number of Module Ways | 10 |
| IP Rating | IP44 |
| Short Circuit Rating kA | 50kA when used with equivalent rated modules |
| Incomer Rating | 250 |
| Maximum Current Rating | 250A |
| Incomer Test Sockets | L1, L2, L3, N & E |
| Lifting Method | Integral fork pockets and vertical crane lifting accessories |

21-11-2024 | 18:00:11