## **Product Specification Sheet**





## MOD.DU-FS3-630A

A robust galvanised sheet steel freestanding MOD.DU enclosure rated 630A. This freestanding MOD.DU enclosure comes with a heavy duty stand suitable for crane lifting or placement by forklift or pallet truck. The MOD.DU enclosures are used for temporary power distribution for environments such as construction sites and other heavy industrial areas. These units are manufactured to the requirements of BS EN 61439-4.

Featuring a 630A 4P Schneider MCCB incomer, located in a segregated end box, consisting of 5no test lead sockets to enable safer onsite testing. The 14W MOD.DU busbar assembly sits within a 900mm width enclosure, compatible with a variety of distribution module options including; hardwire MCCB/RCD subcircuits ranging from 125A-630A, direct connect modules to create a tower crane switch or plant RCD from 125A-630A, segregated 160A MCB modules and commando socket, outlet modules and powerlock modules to create a secure plug and play system. MOD.DU Modules, blanks and additional accessories are purchased separately.



04-04-2025 | 03:31:17

EL-BJORN UK LTD Unit 2 Oyster Park, 109 Chertsey Road, West Byfleet, GB-Surrey, KT14 7AX Phone: (+44) 01483 729 348 E-mail: info@elbjorn.com



## **Product Benefits**

- 630A 4P Schneider MCCB incomer with 5no test lead sockets
- Customisable with interchangeable modules to meet the your power requirements
- Made from galvanised sheet steel with a powder-coated finish to withstand harsh conditions
- Integral fork pockets and vertical crane lifting eyelets make moving and installing effortless
- Includes 14 module ways for streamlined power distribution
- · Contact us directly for purchases

## **Technical Data**

| Product name              | MOD.DU-FS3-630A  |
|---------------------------|--|
| Product Number            | EB16651  |
| Colour                    | El-Björn Blue  |
| Dimensions H x W x D (mm) | 1700 x 1100 x 500  |
| Number of Module Ways     | 14   |
| IP Rating                 | IP44   |
| Short Circuit Rating kA   | 50kA when used with equivalent rated modules                 |
| Incomer Rating            | 630A   |
| Maximum Current Rating    | 630A   |
| Incomer Test Sockets      | L1, L2, L3, N & E  |
| Lifting Method            | Integral fork pockets and vertical crane lifting accessories |

04-04-2025 | 03:31:17

EL-BJORN UK LTD Unit 2 Oyster Park, 109 Chertsey Road, West Byfleet, GB-Surrey, KT14 7AX Phone: (+44) 01483 729 348 E-mail: info@elbjorn.com

